

Suite of **ACUTE CARE SURGERY PRODUCTS**

designed for your portfolio of procedures



A wide range of generator power
to meet multiple procedural needs

Full suite of products offered in
one convenient place

Bovie
Operating with precision™



The Next Generation of Electrosurgical Generators

ELECTROSURGICAL GENERATORS



Unsurpassed 4-year warranty on all Bovie Electrosurgery Generators!



A3350 – OR I PRO 300

Feature: The **dual monopolar ports** allow two surgeons to work simultaneously in the spray coagulation setting.

Benefit: The two surgeons can work in separate areas allowing the procedure to be completed faster.

Feature: The **CUT II** mode has a low peak to peak voltage (Vp-p) of 750Vp-p. This allows for less tissue damage when performing invasive surgical procedures using any procedural scope.

Benefit: When performing a laparoscopic cutting procedure and cauterizing tissue, the **CUT II** mode causes less damage to the tissue allowing for faster healing time. This mode may help prevent direct and capacitance coupling.

Feature: The **Auto Bipolar** setting allows the surgeon to activate the bipolar forceps without a foot pedal.

Benefit: The surgeon does not have to look down to locate the foot pedal allowing for quicker activation of the bipolar forcep saving time and motion during the procedure.

Feature: The **Bovie® Bipolar** has more power than the Macro, Micro, and Standard bipolar settings.

Benefit: This mode provides enough power for the most demanding surgical procedures.

Feature: Gentle Coag Mode

Benefit: This mode provides gentler coagulation when a Gold Probe™* is used during a colonoscopy to prevent perforation of the intestine.

Feature: Split Pad

Benefit: Complete patient safety to prevent burns during procedures just like our larger units in the Operating Room.



A2350 – Surgi-Center I PRO

Feature: The **dual monopolar ports** allow two surgeons to work simultaneously in the spray coagulation setting.

Benefit: The two surgeons can work in separate areas allowing the procedure to be completed faster.

Feature: The **CUT II** mode has a low peak to peak voltage (Vp-p) of 750Vp-p. This allows for less tissue damage when performing invasive surgical procedures using any procedural scope.

Benefit: When performing a laparoscopic cutting procedure and cauterizing tissue, the **CUT II** mode causes less damage to the tissue allowing for faster healing time. This mode may help prevent direct and capacitance coupling.

Feature: The surgeon can move very smoothly from monopolar to bipolar.

Benefit: Saves the surgeon time and motion during the procedures.

Feature: The A2350 Surgi-Center I PRO generator has **four blend settings**.

Benefit: The four blend settings allows the surgeon to customize how much coag they want in the cut setting.

Feature: Split Pad

Benefit: Complete patient safety to prevent burns during procedures just like our larger units in the Operating Room.

*Gold Probe is a product of Boston Scientific

GENERATORS COMPARISON

FEATURES FOR:	A3350	A2350
Cut (# of modes)	✓ 300 W (2)	✓ 200 W (2)
Blend (# of steps)	✓ 200 W (4)	✓ 200 W (4)
Pinpoint Coag	✓ 120 W	✓ 120 W
Fulguration/Spray Coag	✓ 120 W	✓ 120 W
Gentle Coag	✓ 120 W	✓ 120 W
Macro Bipolar	✓ 150 W	✓ 80 W
Standard Bipolar	✓ 50 W	✓ 50 W
Micro Bipolar	✓ 80 W	✓ 80 W
Bovie Bipolar	✓ 225 W	

FEATURES FOR:	A3350	A2350
Pad Alarm	✓	✓
Pad Sensing (tissue impedance)	✓	✓
Presets (# of presets)	✓ (10)	✓ (10)
PENCILS/HANDPIECES FOR:	A3350	A2350
Foot Control	✓	✓
Standard 3-Pin	✓	✓
ESPR2 Reusable Pencil	✓	✓
Two Pencil Configuration	✓	✓
US, Canada	✓	✓
CE	✓	✓

Illuminating the Path to Better Healthcare

MEDICAL LIGHTING

Bovie® offers energy efficient LED Medical Lights to provide 50,000 hours of cool, clear visibility and are ideal for patient exams or small surgical procedure rooms. Control your lighting options with one hand. Bovie Medical Lighting provides a multi-dimming and illumination field that is controlled with a sterilizable handle keeping you in a sterile field.



MI-550



MI-750



MI-1000



System Two LED

Recommended Complementary Products

SMOKE EVACUATION SYSTEM

Smoke Shark™ II

The Bovie Smoke Shark II is designed to be easy to use and is effective for controlling surgical smoke generated from the use of any energy devices including electrosurgical, laser, and ultrasonic products.



SE02 – Smoke Shark unit with pneumatic footswitch (FSSEP)



SERS2 – EZ link remote activation switch for Smoke Shark II



SEPAT – Pencil adaptor for smoke evacuator

MOBILE CART



BV-IDS-CS

PENCILS



ESP1 – Sterile disposable electrosurgical push button pencil



ESP6 – Sterile disposable electrosurgical rocker switch pencil

RETURN ELECTRODES



ESRE – Split adult return electrode



ESREC – Split adult return electrode w/2.8 m cable

Recommended Complementary Products

BIPOLAR & FOOTSWITCH ACCESSORIES



A824 – Reusable bipolar forceps



A827V – Bipolar cable



A1255A – Footswitch adapter



BV-1254B – Bipolar Footswitch



BV-1253B – Monopolar Footswitch

*SPECIALTY ELECTRODES



ES62 – SuperCut™ tungsten needle, super fine 4.5cm, sterile



ES63 – SuperCut tungsten needle, modified super fine 4.5cm, sterile



AR00 – Hook 90 arthroscopic electrode, sterile



AR02 – Acromioplasty arthroscopic electrode, sterile



ES61HS – Disposable SuperCut tungsten needle, modified fine with Heatshrink, sterile



AR01 – Hook 45 arthroscopic electrode, sterile



AR03 – Meniscectomy arthroscopic electrode, sterile

*DISPOSABLE ELECTRODES



ES07 – Extended ball electrode 0.197" (5mm)



ES39 – Extended modified blade electrode 6" (15.24cm)



ES20 – Standard 3/16" ball electrode 0.188" (4.78mm)



ES02 – Standard needle electrode 2.75" (6.99cm)



ES01 – Standard blade electrode 2.75" (6.99cm)

*LAPAROSCOPIC ELECTRODES



LH01 – L-Hook heavy wire with 4mm adaptor, sterile



LH08 – L-Hook wire with 4mm adaptor, sterile



LJ07 – J-Hook wire with 4mm adaptor, sterile



LL06 – Standard blade with 4mm adaptor, sterile



LS05 – Spatula with 4mm adaptor, sterile



LB02 – Ball with 4mm adaptor, sterile

*RESISTICK II™ COATED ELECTRODES



ES58T – Blade electrode 2.5" (6.35cm)



ES39T – Extended modified blade electrode 6" (15.24cm)



ES20T – Standard 3/16" ball electrode 0.188" (4.78mm)



ES02T – Standard needle electrode 2.75" (6.99cm)

*More electrode styles available